

SPECIFICATION

and

PERFORMANCE

for

SWITCHING POWER SUPPLY

M/N : SNP-C043

Reviewed by Project Manager	梁錦章 12-27-05	張惠芬 05-24-06				
Typed by Document Assistant	張惠芬 12-27-05	張惠芬 051806				
SKYNET ELECTRONIC			LAST REV. NO.			

1.0 INTRODUCTIONS

2.0 INPUT SPECIFICATIONS

2.1 Input Voltage

The range of input voltage is from 85VAC to 264VAC, nominal line is 115VAC/230VAC. (Label 100 ~ 240VAC)

2.2 Input Frequency

The range of input frequency is from 47Hz to 63Hz.

2.3 Input Current

The maximum input current is 1.5A at 115VAC or 0.8A at 230VAC.

2.4 Inrush Current

The inrush current will not exceed 30A at 115VAC input or 60A at 230VAC input cold start, 25°C.

3.0 OUTPUT SPECIFICATIONS

3.1 Load range

Output	Min. load	Rated load	max. load	Peak load	voltage accuracy
+5V	0A	4A	6A	8A	+4.95V to +5.05V
+12V	0A	1.5A	2A	3A	+11.4V to 12.6V

At factory, the +5V output is set between +4.95V to +5.05V at 60% rated load and nominal line input. The peak power should be less than 57W and can be supplied up to 8 sec. at nominal line. The total max. output power shall be kept within 38W.

3.2 Ripple and noise

The peak to peak ripple and noise for each output is less than 1% of each output voltage at rated load, nominal line. Measuring is done by 15MHz bandwidth limited oscilloscope and terminated each output with a 0.47uF & 10uF parallel capacitor.

3.3 Line regulation

The output line regulation, for all outputs are less than + -1% while measuring at rated load and + -10% of nominal line input voltage changing.

3.4 Load regulation

The load regulation for +5V, is less than $\pm 2\%$, for +12V is less than $\pm 3\%$ which are measured by changing the output load + -40% from 60% rated load, and the other outputs are kept at 60% rated load and nominal line input.

4.0 GENERAL FEATURES

4.1 Efficiency

The efficiency is 81% typ. while measuring at nominal line and rated load.

4.2 Hold up time

The hold up time is 16ms typ. at 115VAC input and rated load, which is measured from the end of the last charging pulse to when the main output drops down to 95% output voltage.

4.3 Protection

4.3.1 Over voltage protection

The built-in crowbar circuit will shut down the outputs to avoid damaging the external circuits. The trip point of over voltage protection is around +5.7V to +7.0V. To recover from over voltage protection, cycle the AC line OFF and ON is necessary.


4.3.2 Short circuit and over load protection

The power supply will generate a hiccup mode to protect itself against short circuit or over load conditions, and will automatically return to normal after fault conditions are removed.

5.0 ENVIRONMENT SPECIFICATIONS

5.1 Operating temperature

-20°C to 70°C (50°C to 70 °C can operate decreasingly 2.5% / °C from 50 °C)



5.2 Storage temperature

-40°C to +75°C

5.3 Operating humidity

10% to 90% Non-Condensing.

5.4 Altitude

Will operate properly at any altitude between 0 to 6000ft.

6.0 INTERNATIONAL STANDARDS

6.1 Safety standards

Designed to meet the following regulations :

UL 60950

CSA 22.2 NO.234

EN 60950

6.2 EMI standards

Designed to meet the following limits :

FCC docket 20780 curve "B"

EN55022 class "B"




EN61000-3-2 class "A"

6.3 EMS standards



Designed to meet the following limits :

EN61000-4-2	4KV contact, 8KV air discharge	Criterion A
EN61000-4-3	10V/M with 80% AM	Criterion A
EN61000-4-4	4KV	Criterion A
EN61000-4-5	Line to Line 1KV ; Line to ground 2KV.	Criterion A
EN61000-4-6	10V with 80% AM	Criterion A
EN61000-4-8	3A/M	Criterion A
EN61000-4-11	30 % dips 10 ms, Criterion A	
	60 % dips 100 ms, Criterion C	
	95 % dips 5000 ms, Criterion C	

7.0 MECHANICAL SPECIFICATION



Screw protrusion limitation



7.1 Dimensions

Tolerance specified is + -0.4mm between mounting holes, + -0.8mm other dimensions.

7.2 Connectors

TB1--AC Input & DC Output : Terminal Blocks.

7.3 Pin assignment


Pin 1.	AC / L	4.	+12V
2.	AC / N	5.	GND
3.	Earth	6.	+5V

7.4 Packing


Net weight	: 315 g approx. / unit
Carton size (mm)	: 463 (L) x 316 (W) x 287 (H)
Quantity	: 40 units / carton
Gross weight	: 15.6 kg approx. / carton

8.0 PERFORMANCE (input voltage is 115VAC, unless others specified)


8.1 Switching frequency ripple




8.2 Line frequency ripple




8.3 Output turn on wave form




8.4 Output turn off wave form




8.5 Hold-up time



8.6 Over voltage protection




8.7 +5V step response




+5V step from 0.8A to 4A
other output at 60% load

8.8 +12V step response



+12V step from 0.3A to 1.5A
other output at 60% load

8.9 FCC B performance



8.10 EN55022 class "B"

